AMENDMENTS TO THE CLAIMS

Please replace the pending claims with the following claim listing:

1. **(Currently Amended)** A wavelength multiplex transmission system having a transmission apparatus and a receiving apparatus connected via an optical transmission line <u>to</u> <u>transmit an input signal</u>, wherein:

the transmission apparatus is configured to convert differential signals of the input signal to separate optical signals to transmit to the optical transmission line; and

the receiving apparatus is configured to receive the <u>separate</u> optical signals from the optical transmission line to reproduce the differential signals.

- 2. **(Currently Amended)** The wavelength multiplex transmission system according to claim 1, wherein the receiving apparatus further combines the reproduced differential signals to reproduce the input signal.
- 3. **(Previously Presented)** The wavelength multiplex transmission system according to claim 1, wherein the receiving apparatus adjusts a time difference between the reproduced differential signals.

4. **(Currently Amended)** A wavelength multiplex transmission system having a transmission apparatus and a receiving apparatus connected via an optical transmission line, wherein: the transmission apparatus comprises; <u>comprises:</u>

(N+M) optical transmitters (where N is an integer of 2 or more and M is an integer from 1 to N) for transmitting <u>a plurality of</u> input signals as optical signals with different wavelengths,

M differential dividers for differentially dividing M input signals out of the plurality of input signals, respectively, and inputting the differentially divided signals into $2\times M$ optical transmitters out of the (N+M) optical transmitters, respectively, and a wavelength multiplex filter for wavelength multiplexing and outputting the

(N+M) optical signals from the (N+M) optical transmitters, and wherein: the receiving apparatus comprises; comprises:

a wavelength separation filter for separating the wavelength multiplexed optical signals to output (N+M) optical signals;

(N+M) optical receivers for receiving the (N+M) optical signals from the wavelength separation filter, respectively, to output (N+M) output signals; and

M differential combiners, each differentially combining the output signals from the two optical receivers receiving a pair of optical signals which have been differentially divided and transmitted, out of the (N+M) optical receivers, to output one signal.

- 5. **(Currently Amended)** The wavelength multiplex transmission system according to claim 4, wherein the transmission apparatus inputs has two corresponding differential signals from one differential divider into as inputs to two optical transmitters, respectively, and transmits them the two differential signals as separate optical signals with adjacent wavelengths.
- 6. **(Previously Presented)** The wavelength multiplex transmission system according to claim 4, wherein the receiving apparatus is further provided with a delay time controller for adjusting delay time difference between a pair of optical signals on the optical transmission line, at the preceding stage of the differential combiner.

7. **(Currently Amended)** A transmission apparatus for transmitting optical signals, comprising:

optical conversion means for converting differential signals of an input signal to separate optical signals; and

optical transmission means for transmitting the converted optical signals.

8. **(Currently Amended)** The transmission apparatus according to claim 7, wherein: the optical conversion means converts the differential signals to <u>separate</u> optical signals with different wavelengths; and

the optical transmission means multiplexes the <u>separate</u> optical signals with different wavelengths to transmit.

- 9. **(Currently Amended)** The transmission apparatus according to claim 7, further comprising differential divider means for dividing [[an]] the input signal to the differential signals.
 - 10. (Currently Amended) A transmission apparatus comprising:

(N+M) optical transmitters (where N is an integer of 2 or more and M is an integer from 1 to N) for transmitting <u>a plurality of</u> input signals as optical signals with different wavelengths;

M differential dividers for differentially dividing M input signals out of the <u>plurality of</u> input signals, respectively, and inputting the differentially divided signals into 2×M optical transmitters out of the (N+M) optical transmitters, respectively; and

a wavelength multiplex filter for wavelength multiplexing the (N+M) optical signals from the (N+M) optical transmitters to output.

11. **(Currently Amended)** The transmission apparatus according to claim 10, inputting having two corresponding differential signals from one differential divider into as inputs to two optical transmitters, respectively, and transmitting them the two differential signals as separate optical signals with adjacent wavelengths.

12. **(Currently Amended)** A receiving apparatus for receiving optical signals including differential signals of a signal, comprising:

optical receiving means for receiving the optical signals; and optical conversion means for reproducing the differential signals from the optical signals.

13. **(Currently Amended)** The receiving apparatus according to claim 12, wherein: the differential signals are wavelength-multiplexed as <u>separate</u> optical signals with

different wavelengths; and

the optical conversion means reproduces the differential signals from the <u>separate</u> optical signals with different wavelengths.

- 14. **(Previously Presented)** The receiving apparatus according to claim 12, further comprising differential combining means for combining the reproduced differential signals.
- 15. **(Original)** The receiving apparatus according to claim 14, further comprising time difference control means for adjusting time difference between the reproduced differential signals.
 - 16. **(Currently Amended)** A receiving apparatus comprising:

a wavelength separation filter for separating a wavelength multiplexed optical signal to output (N+M) optical signals (where N is an integer of 2 or more and M is an integer from 1 to N);

(N+M) optical receivers for receiving the (N+M) optical signals from the wavelength separation filter, respectively, to output (N+M) output signals; and

M differential combiners, each [[for]] differentially combining the output signals from two optical receivers receiving a pair of optical signals out of the (N+M) optical receivers, to output one signal.

- 17. **(Original)** The receiving apparatus according to claim 16, further comprising a delay time controller for adjusting delay time difference between the pair of two optical signals on the optical transmission line, at the preceding stage of the differential combiner.
- 18. **(Previously Presented)** The wavelength multiplex transmission system according to claim 2, wherein the receiving apparatus adjusts a time difference between the reproduced differential signals.
- 19. **(Previously Presented)** The wavelength multiplex transmission system according to claim 5, wherein the receiving apparatus is further provided with a delay time controller for adjusting delay time difference between a pair of optical signals on the optical transmission line, at the preceding stage of the differential combiner.
- 20. **(Previously Presented)** The transmission apparatus according to claim 8, further comprising differential divider means for dividing an input signal to the differential signals.
- 21. **(Previously Presented)** The receiving apparatus according to claim 13, further comprising differential combining means for combining the reproduced differential signals.